



TECHNICAL DATA SHEET

EASY COLOR® DECO PEARL 900

DESCRIPTION

EASY COLOR® DECO PEARL 900 is a high-gloss 1 component acrylic water-based top and protection clear coat. This ready-to-use and DIY varnish gives a stunning pearl-like effect to design projects.

Destined for the application on solvent and water-based paints, unpainted glass fiber wallpapers, concrete, plaster, wooden panels etc. It offers a high resistance to water and in general to weather conditions.

To obtain color effects, you can use EASY COLOR® UNIVERSAL COLORANT with a maximum of 3% dye.

This highly-decorative top-coat is ideal to give the glamorous shine of natural pearl, adding a touch of sophistication and elegance in your home or hotels on feature walls and accessories.

PRECAUTIONS

- Mix carefully before use.
- Avoid contact with eyes and skin.
- Wear protective clothes, glasses and gloves.
- Keep out of reach of children.
- Keep products away from frost and from heat sources.
- Do not dispose of residual paint by flushing it away.
- Take appropriate precaution when disposing of the packages.
- Consult the Safety Data Sheet for more details.



COPRABEL
Quality in Colors

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7
BE-1300 Wavre Belgium
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89
www.coprabel.com info@coprabel.com



TECHNICAL DATA SHEET

EASY COLOR® DECO PEARL 900

METHOD OF USE

Surface preparation	The painted surface must be clean and completely dry. It is recommended to add a white primer beforehand to highlight the pearl effect.
Application & Dilution	Brush, roller and spray gun. For Spray Gun: - Nozzle: 1,3 to 1,6 mm. - Pressure: 1.5 to 2.5 bar. - Apply 40 microns dry with a viscosity of 30 to 40 sec in a DIN 4 m / 20°C cup. - Wear safety gloves and spray mask. Dilution: water. - brush and roller: dilute with 2% water. - spray gun: dilute with 5 to 10% water.
Drying time	2 hours at 23° C and 50% relative humidity.
Cleaning of Material	With water.
Recoatable	After 12 hours.
Shelf life	1 year in original and sealed can.

TECHNICAL SPECIFICATIONS

Aspect	Pearl effect, transparent liquid.
Composition	Binder: 100% acrylic resin in solution, pearlescent pigment and water.
Thickness Dry Film	15µ on an average.
Solid Content	Weight %: 26.14.
Density	1.02 g/cm ³ at 20°C.
Flash Point	Not applicable.
Coverage	± 8 -11 m ² /L on clean support without any loss.
Packaging	500 ML.



TECHNICAL DATA SHEET

EASY COLOR® DECO PEARL 900

REMARKS AND RECOMMENDATIONS

Store in a well-ventilated and dry room at temperatures between 10°C and 30°C. Higher temperature could have a significant influence on drying time. Relative humidity of the environment: <80%. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

For a long-lasting effect and protection, use EASY COLOR ® ACRYLIC VARNISH (water-based) as a final coat for indoor use.

Warranty invalid if other system than provided by COPRABEL S.A. is used.

Note: Cancels and replaces the former editions. It's up to our customers to check, before application, if it is indeed the latest edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of surface to be treated.