



TECHNICAL DATA SHEET

EASY COLOR® ACRYLIC VARNISH WATER-BASED

DESCRIPTION

Colorless, semi-gloss protective and decorative water-based clear coat for application on surfaces painted with EASY COLOR® solvent and water-based paints or any other paints to protect them from oxidation. This product is suitable for indoor use.

PRECAUTIONS

- Mix carefully before use.
- Avoid contact with eyes and skin.
- Wear protective clothes, glasses and gloves.
- Keep out of reach of children.
- Keep products away from frost and from heat sources.
- Do not dispose of residual paint by flushing it away.
- Take appropriate precaution when disposing of the packages.
- Consult the Safety Data Sheet for more details.

METHOD OF USE

Surface preparation	The painted surface must be clean and completely dry.
Application & Dilution	Brush and roll: dilute with 2% water. Spray Gun: dilute with 5 to 10% water.
Drying time	2 hours.
Recoatable	12 hours. 24 hours on epoxy or PU paint (The surface has to be sanded (P400) before application of the second layer for a better adhesion).
Cleaning of Material	With water
Storage	Store unopened original package in a fresh and well-ventilated room.
Shelf life	2 years in original and sealed can.



TECHNICAL DATA SHEET

EASY COLOR® ACRYLIC VARNISH WATER-BASED

TECHNICAL SPECIFICATIONS

Aspect	Clear, transparent liquid.
Composition	Binder: 100% acrylic resin in solution. Water.
Thickness Dry Film	15µ on an average.
Solid Content	Weight %: 41.87.
Density	1.02 g/cm ³ at 20° C.
Flash Point	Not applicable.
Coverage	± 10 -14m ² /L per coat according to the substrate.
Packaging	500 ML.

REMARKS AND RECOMMENDATIONS

Warranty invalid if other system than provided by COPRABEL S.A. is used.

Note: Cancels and replaces the former editions. It's up to our customers to check, before application, if it is indeed the latest edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of surface to be treated.