



COPRABEL
Quality in Colors

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7
BE-1300 Wavre Belgium
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89
www.coprabel.com info@coprabel.com



TECHNICAL DATA SHEET

EASY COLOR® UNIVERSAL COLORANTS

DESCRIPTION

EASY COLOR® UNIVERSAL COLORANTS are based on concentrated pigments preparations. It is easy-to-use and intended for both professionals and the general public wishing to obtain a light or pastel colour in all solvent or water-based paints.

EASY COLOR® UNIVERSAL COLORANT can be used for colouring water-based, vinyl, acrylic, latex, emulsions, oil and alkyd paints whether glossy, satin or matt, cellulose paint and any paint which is diluted with white spirit. Other uses include: fine shades for artists, incorporation in plastics (e.g. Rigid P.E. foams) and tinting of N.C. or PU lacquers (max 3%) and epoxy paints.

These colorants are UV and weather resistant, except for Yellow 701 and Red Vermillion 705, which are not recommended for outdoor use when they are used in pastel shades.

PRECAUTIONS

- Mix carefully before use.
- Avoid contact with eyes and skin.
- Wear protective clothes, glasses and gloves.
- Keep out of reach of children.
- Keep products away from frost and from heat sources.
- Do not dispose of residual paint by flushing it away.
- Take appropriate precaution when disposing of the packages.
- Consult the Safety Data Sheet for more details.



COPRABEL
Quality in Colors

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7
BE-1300 Wavre Belgium
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89
www.coprabel.com info@coprabel.com



TECHNICAL DATA SHEET

EASY COLOR® UNIVERSAL COLORANTS

METHOD OF USE

Application & Dilution	It is used at different percentages in white or transparent paints. In order to avoid a longer drying time of the paint, do not exceed a dosage of 5% of the paint volume. It is recommended to add the colorant in a small quantity of paint and then add the mixture to the total volume while stirring well until the desired shade is obtained. Notice: - matt paints darken after they have dried. - "textured" paints need less colorants, due to their composition.
Drying	Depends on paint.
Cleaning of Material	With water and soap.
Shelf life	2 years in original and sealed bottle.

TECHNICAL SPECIFICATIONS

Shades	20 different colors.
Composition	Organic or inorganic pigment dispersed in special non-ionic surface-active agent & solvent.
Dry Extract	25 – 60% depending on colour.
Density	1,25 – 2,5 (variable, depending on colour).
Packaging	50 ML – 100 ML – 250 ML – 500 ML – 20L.

REMARKS AND RECOMMENDATIONS

Store in a well-ventilated and dry room at temperatures between 15°C and 25°C. Higher temperature could have a significant influence on drying time. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

Warranty invalid if other system than provided by COPRABEL S.A. is used.

Note: Cancels and replaces the former editions. It's up to our customers to check, before application, if it is indeed the latest edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of surface to be treated.