



**COPRABEL**  
*Quality in Colors*

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7  
BE-1300 Wavre Belgium  
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89  
www.coprabel.com info@coprabel.com



# TECHNICAL DATA SHEET

## EASY COLOR® DECO COPPER 907

---

### DESCRIPTION

---

EASY COLOR® DECO COPPER 907 is a ready-to-use and DIY premium water-based metallic paint that has the same brilliance, adherence and durability as EASY COLOR® COPPER 903 solvent-based paint.

It offers good opacity, regular adherence on substrate and it is odourless. It can be used on all types of applications: wood, metals, walls, ceilings, plaster, moulding, cement, concrete, wallpaper, brick etc., as long as it is applied on an appropriate primer.


DECO COPPER 907 will give a unique metal look to your projects, whether it is used as an accent colour for decorative objects or on larger architectural works.

---

### PRECAUTIONS

---

- Mix carefully before use.
- Avoid contact with eyes and skin.
- Wear protective clothes, glasses and gloves.
- Keep out of reach of children.
- Keep products away from frost and from heat sources.
- Do not dispose of residual paint by flushing it away.
- Take appropriate precaution when disposing of the packages.
- Consult the Safety Data Sheet for more details.



**COPRABEL**  
*Quality in Colors*

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7  
BE-1300 Wavre Belgium  
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89  
www.coprabel.com info@coprabel.com



## TECHNICAL DATA SHEET

### EASY COLOR® DECO COPPER 907

#### METHOD OF USE

Surface preparation	According to the substrates: remove pre-existing paint, degrease with water and soap or washing diluent, sand and dust. Use suitable primer for surfaces in wood, compressed wood, metal ferrous and non-ferrous. The product can be applied directly on new walls or painted, ceilings, plaster, plaster with cardboard, brick, cement, concrete, wall paper, and plaster moulding.
Application & Dilution	Stir thoroughly before and while using. Brush, roll, low pressure spray gun: ready to use.
Drying time	1 hour at 20°C and 60% relative humidity.
Recoatable	After 4 hours.
Cleaning of Material	With water.
Shelf life	2 years in original and sealed can.

#### TECHNICAL SPECIFICATIONS

Aspect	Metallic, Copper.
Composition	Binder: aqueous polymer based on VAE. Pigment: pearlescent. Water.
Thickness Dry film:	10 µ on an average.
Solid Content	Weight %: 32.79.
Density	1.10 g/cm <sup>3</sup> .
Flash Point	Not applicable.
Coverage	± 8 -11 m <sup>2</sup> /L per coat.
Packaging	250 ML - 750 ML.



**COPRABEL**  
*Quality in Colors*

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7  
BE-1300 Wavre Belgium  
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89  
www.coprabel.com info@coprabel.com



# TECHNICAL DATA SHEET

## EASY COLOR® DECO COPPER 907

### REMARKS AND RECOMMENDATIONS

Store in a well-ventilated and dry room at temperatures between 10°C and 30°C. Higher temperature could have a significant influence on drying time. Relative humidity of the environment: <80%. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

For a long-lasting effect and protection, use EASY COLOR® ACRYLIC VARNISH (water-based) as a final coat for indoor use.

Warranty invalid if other system than provided by COPRABEL S.A. is used.

*Note: Cancels and replaces the former editions. It's up to our customers to check, before application, if it is indeed the latest edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of surface to be treated.*